

PearlSol D60



Product Code

Region Africa

Product Category Aliphatic Mineral Solvent

Description PearlSol D60 consists of predominantly C10-C12 paraffins and naphthenes. Low aromatic content, negligible amount of reactive impurities and a low, sweet odour.

Typical Properties

Property	Unit	Method	Value
Density @20°C	kg/L	ASTM D4052	0.786
Appearance	-	Visual	Clear & Bright
Colour	Saybolt	ASTM D156	+30
Distillation, Initial Boiling Point	°C	ASTM D86	189
Distillation, DP	°C	ASTM D86	210
Aromatics	mg/kg	SMS 2728	100
Sulfur	mg/kg	ISO 29846	<0.5
Flash Point	°C	ASTM D93	67
Aniline Point	°C	ASTM D611	71
Copper Corrosion	-	ASTM D130	1
Kinematic Viscosity	CST	ASTM 445	1.6

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM) : www.astm.org

International Organization for Standardization (ISO) : www.iso.org

Disclaimer

All products purchased or supplied by PearlChem are tested in accordance with PearlChem quality system. PearlChem does not guarantee the typical values. Typical values quoted are intended as general guidelines only and are not necessarily representative of the actual batch. PearlChem reserves the right to use other equivalent test methods in certifying products. The use of PearlChem's products must be guided by the user's own methods to determine the products' suitability for a particular purpose. All products purchased or supplied by PearlChem are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading.